

VRV IV S-series heat pump

RXYSQ-TV1/RXYSQ-TY1



Space saving solution without compromising on efficiency

- › Space saving trunk design for flexible installation
- › Covers all thermal needs of a building via a single point of contact: accurate temperature control, ventilation, air handling units and Biddle air curtains
- › Wide range of indoor units: either connect VRV or stylish indoor units such as Daikin Emura, Nexura ...
- › Incorporates VRV IV standards & technologies: Variable Refrigerant Temperature and full inverter compressors

RXYSQ-TV1/TY1




RXYSQ4-6TV1/TY1

Outdoor unit		RXYSQ-TV1/RXYSQ-TY1	4TV1	5TV1	6TV1	4TY1	5TY1	6TY1	8TY1	10TY1	12TY1		
Capacity range		HP	4	5	6	4	5	6	8	10	12		
Cooling capacity	Nom.	35°CDB	kW	12.1	14.0	15.5	12.1	14.0	15.5	22.4	33.5		
	Max.	6°CWB	kW	12.1	14.0	15.5	12.1	14.0	15.5	22.4	33.5		
Heating capacity	Nom.	6°CWB	kW	14.2	16.0	18.0	14.2	16.0	18.0	25.0	37.5		
	Max.	6°CWB	kW	14.2	16.0	18.0	14.2	16.0	18.0	25.0	37.5		
Power input - 50Hz	Cooling	Nom.	35°CDB	kW	3.03	3.73	4.56	3.03	3.73	4.56	6.12	10.2	
		Heating	Nom.	6°CWB	kW	2.68	3.27	3.97	2.68	3.27	3.97	5.20	8.19
	Max.	6°CWB	kW	3.43	4.09	5.25	3.43	4.09	5.25	6.22	8.33	10.2	
Maximum number of connectable indoor units			64 (1)										
Indoor index connection	Min.		50	62.5	70	50	62.5	70	100	125	150		
	Nom.												
	Max.		130	162.5	182	130	162.5	182	260	325	390		
Dimensions	Unit	HeightxWidthxDepth	mm						1,430x940x320		1,615x940x460		
Weight	Unit		kg						104		144		
Fan	Air flow rate	Cooling	Nom.	m ³ /min									
				106						140		182	
Sound power level	Cooling	Nom.	dBA		68	69	70	68	69	70	73	74	76
			dBA		50	51		50	51		55		57
Operation range	Cooling	Min.~Max.	°CDB		-5~46						-5~52		
	Heating	Min.~Max.	°CWB		-20~15.5								
Refrigerant	Type	R-410A											
	Charge	kg		3.6						4.5		7	
	TCO ₂ eq		7.5						9.4		14.6		
Piping connections	Liquid	OD	mm		9.52						12.7		
			mm		15.9		19.1		15.9		19.1		
	Gas	OD	mm		300 (VRV indoor) / 140 RA indoor						22.2		
Power supply	Phase/Frequency/Voltage	Hz/V		1N~/50/220-240						3N~/50/380-415			
		Maximum fuse amps (MFA)	A		32						16		25

(1) Actual number of units depends on the indoor unit type (VRV DX indoor, RA DX indoor, etc.) and the connection ratio restriction for the system (being; 50% ≤ CR ≤ 130%).

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN 16-233 09/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.